

PRODUCT NAME	WOOD SPECIES	PRODUCT SPECIFICATION		CHARACTERISTIC	
BIRCH PLYWOOD	FACE/BACK: BIRCH WOOD CORE: FALCATA/RUBBER OR FALCATA	MOISTURE CONTENT: MAX 14% DENSITY: - CORE FALCATA/RUBBER WOOD = 500-550 KG/CBM - CORE FALCATA WOOD = 320-450 KG/CBM ADHESIVE: T2-UREA FORMALDEHYDE GLUE FORMALDEHYDE EMISSION: AVAILABLE: - CARB PHASE 2 FORMALDEHYDE EMISSION LEVEL		- "READY TO USE" PANEL - FLAT AND SMOOTH SURFACE - DIMENSIONALLY STABLE - DURABILITY BASED PRODUCTS - GOOD ABSORBANCE MATERIAL FOR PAINT - SUSTAINABLE WOOD PRODUCT	
SIZE DETAILS		THICKNESS (MM)	WIDTH (MM)	LENGTH (MM)	CONSTRUCTION
		5,2 MM	1220 MM (4')	2440 mm (8')	FROM 5 PLIES UP TO 9 PLIES DEPEND ON THICKNESS
		9,0 MM			
		12,0 MM			
		15,0 MM			
		18,0 MM			
PACKING DETAILS		THICKNESS	DIMENSION (MM)	40' HC CONTAINER	
		5,2 MM	1220 MM X 2440 MM (4' X 8')	NO. OF CRATES	NO. OF SHEETS
		9,0 MM		18	3240 PCS
		12,0 MM		18	1800 PCS
		15,0 MM		18	1350 PCS
		18,0 MM		18	1080 PCS
		18,0 MM		18	900 PCS
CERTIFICATION LIST FOR BIRCH PLYWOOD	CERTIFICATE DESCRIPTION	CERTIFICATE LOGO	AVAILABILITY ON PLANT		
			SGS-BALARAJA	SGS-BUTUH	SGS-JOMBANG
ISO 9001:2015	SERTIFIKASI MANAJEMEN MUTU		V	X	X
ISO 14001:2015	SERTIFIKASI SITEM MANAJEMEN LINGKUNGAN		V	X	X
CARB	CALIFORNIA AIR RESOURCE BOARD PHASE 2	CARB PHASE 2	V	V	V

US EPA	UNITED STATES ENVIRONMENTAL PROTECTION AGENCY, THE TOXIC SUBSTANCE CONTROL ACT TITLE VI	US EPA TSCA TITLE VI	V	V	V
GREEN LABEL SINGAPORE	GREEN LABEL SINGAPORE (REGISTRATION NUMBER: 035-112-2023)		V	X	X
INDONESIA LEGAL WOOD	SISTEM VERIFIKASI LEGALITAS KAYU		V	V	V